

# リボンヒーター

AC100V 100W用	
形式	巾×長さ(mm)
C10-2010	20×1,000
C10-2510	25×1,000
C10-3010	30×1,000
C10-3510	35×1,000
C10-4010	40×1,000
C10-5010	50×1,000
C10-10010	100×1,500
C10-2015	20×1,500
C10-2515	25×1,500
C10-3015	30×1,500
C10-3515	35×1,500
C10-4015	40×1,500
C10-5015	50×1,500
C10-10015	100×1,500
C10-2020	20×2,000
C10-2520	25×2,000
C10-3020	30×2,000
C10-3520	35×2,000
C10-4020	40×2,000
C10-5020	50×2,000
C10-10020	100×2,000
C10-2030	20×3,000
C10-2530	25×3,000
C10-3030	30×3,000
C10-3530	35×3,000
C10-4030	40×3,000
C10-5030	50×3,000
C10-10030	100×1,000

AC100V 150W用	
形式	巾×長さ(mm)
C15-2010	20×1,000
C15-2510	25×1,000
C15-3010	30×1,000
C15-3510	35×1,000
C15-4010	40×1,000
C15-5010	50×1,000
C15-10010	100×1,000
C15-2015	20×1,500
C15-2515	25×1,500
C15-3015	30×1,500
C15-3515	35×1,500
C15-4015	40×1,500
C15-5015	50×1,500
C15-10015	100×1,500
C15-2020	20×2,000
C15-2520	25×2,000
C15-3020	30×2,000
C15-3520	35×2,000
C15-4020	40×2,000
C15-5020	50×2,000
C15-10020	100×2,000
C15-2030	20×3,000
C15-2530	25×3,000
C15-3030	30×3,000
C15-3530	35×3,000
C15-4030	40×3,000
C15-5030	50×3,000
C15-10030	100×3,000
C15-2040	20×4,000
C15-2540	25×4,000
C15-3040	30×4,000
C15-3540	35×4,000
C15-4040	40×4,000
C15-5040	50×4,000
C15-10040	100×4,000
C15-2050	20×5,000
C15-2550	25×5,000
C15-3050	30×5,000
C15-3550	35×5,000
C15-4050	40×5,000
C15-5050	50×5,000
C15-10050	100×5,000

AC100V 200W用	
形式	巾×長さ(mm)
C20-2010※	20×1,000
C20-2510	25×1,000
C20-3010	30×1,000
C20-3510	35×1,000
C20-4010	40×1,000
C20-5010	50×1,000
C20-10010	100×1,000
C20-2015	20×1,500
C20-2515	25×1,500
C20-3015	30×1,500
C20-3515	35×1,500
C20-4015	40×1,500
C20-5015	50×1,500
C20-10015	100×1,500
C20-2020	20×2,000
C20-2520	25×2,000
C20-3020	30×2,000
C20-3520	35×2,000
C20-4020	40×2,000
C20-5020	50×2,000
C20-10020	100×2,000
C20-2030	20×3,000
C20-2530	25×3,000
C20-3030	30×3,000
C20-3530	35×3,000
C20-4030	40×3,000
C20-5030	50×3,000
C20-10030	100×3,000
C20-2040	20×4,000
C20-2540	25×4,000
C20-3040	30×4,000
C20-3540	35×4,000
C20-4040	40×4,000
C20-5040	50×4,000
C20-10040	100×4,000
C20-2050	20×5,000
C20-2550	25×5,000
C20-3050	30×5,000
C20-3550	35×5,000
C20-4050	40×5,000
C20-5050	50×5,000
C20-10050	100×5,000

AC100V 300W用	
形式	巾×長さ(mm)
C30-2010※	20×1,000
C30-2510※	25×1,000
C30-3010※	30×1,000
C30-3510※	35×1,000
C30-4010	40×1,000
C30-5010	50×1,000
C30-10010	100×1,000
C30-2015※	20×1,500
C30-2515	25×1,500
C30-3015	30×1,500
C30-3515	35×1,500
C30-4015	40×1,500
C30-5015	50×1,500
C30-10015	100×1,500
C30-2020	20×2,000
C30-2520	25×2,000
C30-3020	30×2,000
C30-3520	35×2,000
C30-4020	40×2,000
C30-5020	50×2,000
C30-10020	100×2,000
C30-2030	20×3,000
C30-2530	25×3,000
C30-3030	30×3,000
C30-3530	35×3,000
C30-4030	40×3,000
C30-5030	50×3,000
C30-10030	100×3,000
C30-2040	20×4,000
C30-2540	25×4,000
C30-3040	30×4,000
C30-3540	35×4,000
C30-4040	40×4,000
C30-5040	50×4,000
C30-10040	100×4,000
C30-2050	20×5,000
C30-2550	25×5,000
C30-3050	30×5,000
C30-3550	35×5,000
C30-4050	40×5,000
C30-5050	50×5,000
C30-10050	100×5,000

■仕様

使用温度	常用温度: 300°C 最高温度: 400°C
規格品寸法	巾 20 mm ~ 100 mm 長さ 1,000 mm ~ 5,000 mm
ワット密度	0.4~0.7 W/cm <sup>2</sup>
付帯部品	電源端子(コンセントプラグ, 丸端子など) リード線 500 mm, 巻き付け用ガラスヒモ

AC100V 400W用	
形 式	巾×長さ(mm)
C40-4010※	40×1,000
C40-5010	50×1,000
C40-10010	100×1,000
C40-2515※	25×1,500
C40-3015※	30×1,500
C40-3515	35×1,500
C40-4015	40×1,500
C40-5015	50×1,500
C40-10015	100×1,500
C40-2020※	20×2,000
C40-2520	25×2,000
C40-3020	30×2,000
C40-3520	35×2,000
C40-4020	40×2,000
C40-5020	50×2,000
C40-10020	100×2,000
C40-2030	20×3,000
C40-2530	25×3,000
C40-3030	30×3,000
C40-3530	35×3,000
C40-4030	40×3,000
C40-5030	50×3,000
C40-10030	100×3,000
C40-2040	20×4,000
C40-2540	25×4,000
C40-3040	30×4,000
C40-3540	35×4,000
C40-4040	40×4,000
C40-5040	50×4,000
C40-10040	100×4,000
C40-3050	30×5,000
C40-3550	35×5,000
C40-4050	40×5,000
C40-5050	50×5,000
C40-10050	100×5,000

AC100V 500W用	
形 式	巾×長さ(mm)
C50-4010※	40×1,000
C50-5010※	50×1,000
C50-10010	100×1,000
C50-4015※	40×1,500
C50-5015	50×1,500
C50-10015	100×1,500
C50-2020※	20×2,000
C50-2520※	25×2,000
C50-3020	30×2,000
C50-3520	35×2,000
C50-4020	40×2,000
C50-5020	50×2,000
C50-10020	100×2,000
C50-2030※	20×3,000
C50-2530	25×3,000
C50-3030	30×3,000
C50-3530	35×3,000
C50-4030	40×3,000
C50-5030	50×3,000
C50-10030	100×3,000
C50-2040	20×4,000
C50-2540	25×4,000
C50-3040	30×4,000
C50-3540	35×4,000
C50-4040	40×4,000
C50-5040	50×4,000
C50-10040	100×4,000
C50-2050	20×5,000
C50-2550	25×5,000
C50-3050	30×5,000
C50-3550	35×5,000
C50-4050	40×5,000
C50-5050	50×5,000
C50-10050	100×5,000

AC100V 600W用	
形 式	巾×長さ(mm)
C60-10010	100×1,000
C60-4015※	40×1,500
C60-5015	50×1,500
C60-10015	100×1,500
C60-2020※	20×2,000
C60-2520※	25×2,000
C60-3020※	30×2,000
C60-3520※	35×2,000
C60-4020	40×2,000
C60-5020	50×2,000
C60-10020	100×2,000
C60-2030※	20×3,000
C60-2530	25×3,000
C60-3030	30×3,000
C60-3530	35×3,000
C60-4030	40×3,000
C60-5030	50×3,000
C60-10030	100×3,000
C60-2040	20×4,000
C60-2540	25×4,000
C60-3040	30×4,000
C60-3540	35×4,000
C60-4040	40×4,000
C60-5040	50×4,000
C60-10040	100×4,000
C60-3050	30×5,000
C60-3550	35×5,000
C60-4050	40×5,000
C60-5050	50×5,000
C60-10050	100×5,000

AC100V 1KW用	
形 式	巾×長さ(mm)
C100-4020※	40×2,000
C100-5020※	50×2,000
C100-10020	100×2,000
C100-3030※	30×3,000
C100-3530※	35×3,000
C100-4030※	40×3,000
C100-5030	50×3,000
C100-10030	100×3,000
C100-4040	40×4,000
C100-5040	50×4,000
C100-10040	100×4,000
C100-4050	40×5,000
C100-5050	50×5,000
C100-10050	100×5,000

AC100V 2KW用	
形 式	巾×長さ(mm)
C200-5030※	50×3,000
C200-10030	100×3,000
C200-10050	100×5,000

※印が付けられている製品は、ワット密度が高く注意を要するため、ご注文の際は、ご確認下さい。

# クリーンルーム用リボンヒーター

## ■仕様

使用温度	常用温度: 200°C
	最高温度: 240°C
規格品寸法	巾 20 mm ~ 50 mm
	長さ 1,000 mm ~ 3,000 mm
ワット密度	0.2~0.3 W/cm <sup>2</sup>
付帯部品	電源端子(コンセントプラグ, 丸端子など)
	テフロンリード線 500 mm
	巻き付け用テクノーラヒモ

## ■型式

ヒーター容量	長さr/m	巾 20m/m	巾 25m/m	巾 30m/m	巾 40m/m	巾 50m/m
100W	1000	CR10-2010	CR10-2510	CR10-3010	CR10-4010	CR10-5010
	1500	CR10-2015	CR10-2515	CR10-3015	CR10-4015	CR10-5015
	2000	CR10-2020	CR10-2520	CR10-3020	CR10-4020	CR10-5020
	3000	CR10-2030	CR10-2530	CR10-3030	CR10-4030	CR10-5030
150W	1000	—	—	CR15-3010	CR15-4010	CR15-5010
	1500	CR15-2015	CR15-2515	CR15-3015	CR15-4015	CR15-5015
	2000	CR15-2020	CR15-2520	CR15-3020	CR15-4020	CR15-5020
	3000	CR15-2030	CR15-2530	CR15-3030	CR15-4030	CR15-5030
200W	1000	—	—	CR20-3010※	CR20-4010	CR20-5010
	1500	CR20-2015	CR20-2515	CR20-3015	CR20-4015	CR20-5015
	2000	CR20-2020	CR20-2520	CR20-3020	CR20-4020	CR20-5020
	3000	CR20-2030	CR20-2530	CR20-3030	CR20-4030	CR20-5030
300W	1000	—	—	CR30-3010※	CR30-4010※	CR30-5010
	1500	—	—	CR30-3015※	CR30-4015	CR30-5015
	2000	—	—	CR30-3020	CR30-4020	CR30-5020
	3000	CR30-2030	CR30-2530	CR30-3030	CR30-4030	CR30-5030
400W	1500	—	—	—	—	CR40-5015※
	2000	—	—	CR40-3020	CR40-4020	CR40-5020
	3000	—	—	CR40-3030	CR40-4030	CR40-5030
500W	1500	—	—	—	—	CR50-5015※
	2000	—	—	CR50-3020	CR50-4020	CR50-5020
	3000	—	—	CR50-3030	CR50-4030	CR50-5030

※印が付けられている製品は、ワット密度が高く注意を要するため、ご注文の際は、ご確認下さい。